



Specifications Philips LED Panel TrueLine SM530C  
28W 4000lm - 940 Cool White | 117x5.5cm - UGR <19 -  
Best Colour Rendering - Motion and Light Sensor

[View Product](#)

## General Information

|                          |                                        |
|--------------------------|----------------------------------------|
| SKU                      | 243295                                 |
| EAN                      | 8718699980221                          |
| Brand                    | Philips                                |
| Manufacturer Name        | SM530C LED40S/940 SRD U4 PI3 L1170 ALU |
| Any Lamp all-in warranty | 5 Years                                |
| Average Lifetime (h)     | 50000                                  |
| Series                   | Panel Led                              |

## Technical Information

|                             |                    |
|-----------------------------|--------------------|
| Technology                  | LED Integrated     |
| Replaces (Watt)             | 2x36               |
| Wattage                     | 28                 |
| Voltage (V)                 | 220-240            |
| Dimmable                    | Dimmable with Dali |
| Colour Code                 | 940 Cool White     |
| Colour temperature (Kelvin) | 4000 Cool White    |
| Colour Rendering (Ra)       | 90-99              |
| Colour of Light             | White              |
| Light colour options        | Single Color       |
| Luminous Flux (Lumen)       | 4000               |

|                          |                               |
|--------------------------|-------------------------------|
| Luminous Efficacy (lm/W) | 143                           |
| IP-rating                | IP20                          |
| Impact Protection (IK)   | IK02 - 0.20 joule             |
| Fixture Connection       | PI [Push-in connector 3-pole] |
| Power factor             | >0.90                         |
| Product Type Category    | LED Panel                     |

## Fixture Information

|                       |                                |
|-----------------------|--------------------------------|
| Mounting Method       | Recessed                       |
| Unified Glare Rating  | < 19 - for offices and schools |
| Optical Cover         | PS (Polystyrene)               |
| Operating Temperature | -10 to +25                     |
| Emergency Lighting    | No Emergency Unit              |
| Colour of the Fixture | Aluminium                      |
| Housing               | Steel                          |
| Colour of material    | Aluminium                      |

## Dimensions

|                |           |
|----------------|-----------|
| LED panel size | 117x5.5cm |
| Length (mm)    | 1170      |
| Width (mm)     | 55        |
| Height (mm)    | 88        |

## Why Any-lamp?

## Sensor Information

Type of sensor



Order from the **largest lighting specialist** in Europe

No Sensor



**Customised** quotation



Up to **7 years warranty**



**Easy** return process